SPOILER ADHESIVE COMPONENT B



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

ISSUE DATE: 14.01.2015 REVISION DATE: 10.03.2021 SUPERSEDES DATE: 10.06.2020

VERSION: 5.0

1. SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name Spoiler Adhesive Component B **Product code** Ford Internal Ref.: 130445

SDS Number 7675

Product use Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Adhesives, sealants
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Supplier Distributor

Ford-Werke GmbH Ford Motor Company Ltd.
Edsel-Ford-Str. 2-14 Parts Distribution Centre
50769 Cologne Royal Oak Way South

Germany NN11 8NT Daventry, Northants

+49 221 90-33333 United Kingdom sdseu@ford.com +44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH - 24/7)

2. SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008

Health hazards	Acute toxicity (inhal.), Category 4	H332	Harmful if inhaled.
	Skin corrosion/irritation, Category 2	H315	Causes skin irritation.
	Serious eye damage/eye irritation, Category 2	H319	Causes serious eye irritation.
	Respiratory sensitisation, Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	Skin sensitisation, Category 1	H317	May cause an allergic skin reaction.
	Carcinogenicity, Category 2	H351	Suspected of causing cancer.
	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335	May cause respiratory irritation.
	Specific target organ toxicity — Repeated exposure, Category 2	H373	May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008

Hazard pictograms



Signal word Danger

Contains 4,4'-methylenediphenyl diisocyanate; 4,4'-methylenediphenyl diisocyanate,

oligomers

Hazard statements

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.
H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention

P260 Do not breathe dust, fume, gas, mist, spray, vapours.

P280 Wear protective gloves, eye protection.

P284 In case of inadequate ventilation wear respiratory protection.

Response

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER, doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

Supplemental hazard information

Extra phrases As from 24 August 2023 adequate training is required before industrial or

professional use.

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII. This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

3. SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008	Notes
4,4'-methylenediphenyl diisocyanate, oligomers	25686-28-6 500-040-3 01-2119457013-49- XXXX	10 - < 20	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	(0.1 ≤C < 100) Resp. Sens. 1, H334 (5 ≤C < 100) Skin Irrit. 2, H315 (5 ≤C < 100) Eye Irrit. 2, H319 (5 ≤C < 100) STOT SE 3, H335 (Note 2)(Note C)

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008	Notes
4,4'-methylenediphenyl diisocyanate	101-68-8 202-966-0 615-005-00-9 01-2119457014-47- XXXX	1-<5	Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Resp. Sens. 1, H334 Skin Sens. 1, H317 Carc. 2, H351 STOT SE 3, H335 STOT RE 2, H373	(0.1 ≤C ≤ 100) Resp. Sens. 1, H334 ($5 \le C \le 100$) Eye Irrit. 2, H319 ($5 \le C \le 100$) Skin Irrit. 2, H315 ($5 \le C \le 100$) STOT SE 3, H335 (Note C)(Note 2)

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

4. SECTION 4: First aid measures

4.1. Description of first aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take

precautions to protect themselves.

Inhalation Remove person to fresh air and keep comfortable for breathing. Call a poison

center or a doctor if you feel unwell.

Skin contact: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation

or rash occurs: Get medical advice/attention.

Eyes contact Rinse immediately and thoroughly, pulling the eyelids well away from the eye (15

minutes minimum). Remove contact lenses, if present and easy to do. Continue

rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion Call a poison center or a doctor if you feel unwell. Do NOT induce vomiting.

Rinse mouth thoroughly. If vomiting occurs, keep head low so that stomach

content doesn't get into the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects: May cause damage to organs through prolonged or repeated exposure.

Suspected of causing cancer.

Symptoms/effects after inhalation Harmful if inhaled. May cause respiratory irritation. May cause allergy or asthma

symptoms or breathing difficulties if inhaled.

Symptoms/effects after skin contact Causes skin irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

5. SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray. Dry powder. Alcohol resistant foam. Carbon dioxide.

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Explosion hazard Heat may cause pressure rise with explosion of tanks/drums.

Reactivity in case of fireDuring fire, gases hazardous to health may be formed. Reacts with water.

Hazardous combustion products

During fire, gases hazardous to health may be formed. Carbon oxides (CO,

CO2). Nitrogen oxides. Hydrogen cyanide.

5.3. Advice for firefighters

> Firefighting instructions Use standard firefighting procedures and consider the hazards of other involved

Do not attempt to take action without suitable protective equipment. Self-Protection during firefighting

contained breathing apparatus. Complete protective clothing.

6. SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment Wear appropriate protective equipment and clothing during clean-up. For further

information refer to section 8: "Exposure controls/personal protection".

Keep unnecessary personnel away. Keep people away from and upwind of **Emergency procedures**

spill/leak. Ventilate spillage area. Do not breathe dust, fume, gas, mist, spray, vapours. Avoid contact with skin and eyes. Local authorities should be advised if

significant spillages cannot be contained.

For emergency responders

Do not attempt to take action without suitable protective equipment. For further Protective equipment

information refer to section 8: "Exposure controls/personal protection".

Keep unnecessary personnel away. **Emergency procedures**

Avoid release to the environment. Avoid discharge into drains, water courses or 6.2. **Environmental precautions**

onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

For containment Stop leak without risks if possible. Move containers from fire area if it can be

done without personal risk.

Methods for cleaning up Large Spills: Stop leak if safe to do so. Dike the spilled material, where this is

possible. Cover with plastic sheet to prevent spreading. Absorb remaining liquid with sand or inert absorbent and remove to safe place. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (for example cloth). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

Other information Dispose of materials or solid residues at an authorized site.

For further information refer to section 8: "Exposure controls/personal 6.4. Reference to other sections

protection". For disposal of residues refer to section 13: "Disposal

considerations".

7. SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling Ensure good ventilation of the work station. Obtain special instructions before

> use. Avoid release to the environment. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Do not breathe dust, fume, gas, mist, spray, vapours. Do not handle until all safety precautions have been read

and understood.

Always observe good personal hygiene measures, such as washing after Hygiene measures

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Store locked up. Keep container tightly closed. Protect from moisture. Store in a

dry, cool and well-ventilated place. Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No smoking.

Maximum storage period 12 months 10 - 30 °C Storage temperature

Special rules on packaging Keep only in original container.

7.3. Specific end use(s)

8. SECTION 8: Exposure controls/personal protection

8.1. Control parameters

United	Kingdom

4,4'-methylenediphenyl diisocyanate, oligomers (25686-28-6)

Regulation	Substance		Туре	Value
EH40/2005 (Fourth edition, 2020). HSE	Di-"isononyl" phtha (28553-12-0) Diisononyl phthalate	alate	WEL TWA (OEL TWA) [1]	5 mg/m³
EH40/2005 (Third edition, 2018). HSE	Isocyanates, all (as Isocyanates	-NCO)	WEL TWA (OEL TWA) [1]	0.02 mg/m³ all (as –NCO) Except methyl isocyanate
			WEL STEL (OEL STEL)	0.07 mg/m³ all (as –NCO) Except methyl isocyanate
			Remark (WEL)	Sen (Capable of causing occupational asthma)
DNEL: Derived no effect	ct level			
No data available				
Components	Туре	Route	Value	Form
Di-"isononyl" phthalate	Worker	Dermal	366 mg/kg bodyweight/day	/ Long-term - systemic effects
(28553-12-0)		Inhalation	51.72 mg/m³	Long-term - systemic effects
	Consumer	Oral	4.4 mg/kg bodyweight/day	Long-term - systemic effects
		Inhalation	15.3 mg/m³	Long-term - systemic effects
		Dermal	220 mg/kg bodyweight/day	• •
4,4'-methylenediphenyl	Worker	Inhalation	0.1 mg/m³	Acute - local effects
diisocyanate (101-68-8)		Inhalation	0.05 mg/m³	Long-term - local effects
	Consumer	Inhalation	0.05 mg/m³	Acute - local effects
		Inhalation	0.025 mg/m³	Long-term - local effects
4,4'-methylenediphenyl	Worker	Inhalation	0.1 mg/m³	Acute - local effects
diisocyanate, oligomers		Inhalation	0.05 mg/m³	Long-term - local effects
(25686-28-6)	Consumer	Inhalation	0.05 mg/m³	Acute - local effects
		Inhalation	0.025 mg/m³	Long-term - local effects
PNEC: Predicted no eff	ect concentration			
No data available	_			_
Components	Туре	Route	Value	Form
Di-"isononyl" phthalate (28553-12-0)	Not applicable	Soil	30 mg/kg dwt	
4,4'-methylenediphenyl	Not applicable	Freshwater	1 mg/l	
diisocyanate (101-68-8)		Seawater	0.1 mg/l	
		Freshwater	10 mg/l	Intermittent release
		Soil	1 mg/kg dwt	
		STP	1 mg/l	

1 mg/l

0.1 mg/l

10 mg/l

Intermittent release

Freshwater

Seawater

Freshwater

Not applicable

Soil 1 mg/kg dwt STP 1 mg/l

8.2. Exposure controls

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used.

Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not

been established, maintain airborne levels to an acceptable level

Materials for protective clothing Personal protection equipment should be chosen according to the CEN

standards and in discussion with the supplier of the personal protective

equipment

Individual protection measures, such as personal protective equipment (PPE)

Eye protection Safety glasses with side shields. EN 166.

Skin protection

Hand protection The recommendation is only valid for the supplied product and the stated

application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the

recommended glove

Liquid

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0.4	Glove recommendation: Camatril Velours® 730 (Kächele- Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0.4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
Other protective	measures	handling the material	d personal hygiene measures, such as washing after and before eating, drinking, and/or smoking. Routinely nd protective equipment to remove contaminants.
Respiratory protection	on	•	e ventilation] wear respiratory protection. Respiratory n a combined gas and particle filter
Skin and body prote	ction	Long sleeved protect	ive clothing,EN ISO 13982,EN 14605
Thermal hazard prote	ection	Wear appropriate the	ermal protective clothing, when necessary.
Environmental expos	sure controls		anagerial or supervisory personnel of all environmental use to the environment.

9. SECTION 9: Physical and chemical properties

Dhysical state

9.1. Information on basic physical and chemical properties

Physical state	Liquia
Appearance	Paste.
Colour	Black.
Odour	Sweet.
Odour threshold	No data available
pH	No data available
Relative evaporation rate (butylacetate=1)	No data available
Melting point	Not applicable
Freezing point	No data available
Boiling point	No data available
Flash point	> 100 °C (closed cup)
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Flammability (solid, gas)	Not applicable
Vapour pressure	No data available
Relative vapour density at 20 °C	No data available
Relative density	1.04 ASTM D1475
Solubility	No data available

Log PowNo data availableViscosity, kinematicNo data available

Viscosity, dynamic 30 – 100 Pa·s Brookfield RTV no 7, 10rpm, 23°C

Explosive propertiesNo data availableOxidising propertiesNo data availableExplosive limitsNo data available

9.2. Other information

VOC (EU) 0 %

10. SECTION 10: Stability and reactivity

10.1. Reactivity The product is non-reactive under normal conditions of use, storage and

transport.

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials Acids. alcohols. Amines. Aqueous solution. Ammonia. Bases. Strong oxidizing

agent. Moisture.

10.6. Hazardous decomposition products During fire, gases hazardous to health may be formed. Carbon oxides (CO,

CO2). Isocyanates.

11. SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity Harmful if inhaled.

Mixture

Name	Method	Type	Exposure route	Value	Unit	Species	Remarks
Spoiler Adhesive Component B		ATE	Inhalation	1 - 5	mg/l/4h		(calculated value)
Substance							
Name	Method	Type	Exposure route	Value	Unit	Species	Remarks
4,4'-methylenediphenyl diisocyanate (101-68-8)	(acc. CLP 3.1.2)	ATE	Inhalation	11	mg/l/4h		vapours
	(acc. CLP 3.1.2)	ATE	Inhalation	1,5	mg/l/4h		dust, mist
4,4'-methylenediphenyl diisocyanate, oligomers (25686-28-6)		LC50	Inhalation	0,387- 0,49	mg/l/4h	rat	
Skin corrosion/irritation	n		Causes skin irritation	n.			
Serious eye damage/iri	ritation		Causes serious eye	irritation.			
Respiratory or skin ser	nsitisation		May cause allergy o cause an allergic sk			or breathing di	fficulties if inhaled. May
Additional information			Persons suffering from with the product.	om allergio	reactions t	o isocyanates	s should avoid contact
Germ cell mutagenicity	1		Based on available	data, the c	lassification	n criteria are r	ot met
Carcinogenicity			Suspected of causin	ng cancer.			
Reproductive toxicity			Based on available	data, the c	lassification	n criteria are r	ot met
STOT-single exposure			May cause respirato	ory irritation	n.		
STOT-repeated exposu	ire		May cause damage	to organs	through pro	olonged or rep	peated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met

Potential adverse human health effects

and symptoms

Information on Effects: refer to section 4.

12. SECTION 12: Ecological information

12.1. Toxicity

Ecology - general The product is not classified as environmentally hazardous. However, this does

not exclude the possibility that large or frequent spills can have a harmful or

damaging effect on the environment.

12.2. Persistence and degradability

No additional information available.

12.3. Bioaccumulative potential

No additional information available.

12.4. Mobility in soil

No additional information available.

12.5. Results of PBT and vPvB assessment

Spoiler Adhesive Component B

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Other adverse effects

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical

ozone creation potential, endocrine disruption, global warming potential) are

expected from this product.

13. SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) Empty containers or liners may retain some product residues. This material and

its container must be disposed of in a safe manner (see: Disposal instructions).

Waste treatment methods Collect and reclaim or dispose in closed containers at licensed waste disposal

site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting

instructions.

Product/Packaging disposal

recommendations

Since emptied containers may retain product residue, follow label warnings even

after container is emptied. Empty containers should be taken to an approved

waste handling site for recycling or disposal.

Additional information Dispose in accordance with all applicable regulations.

European List of Waste (LoW) code

The Waste code should be assigned in discussion between

the user, the producer and the waste disposal company.

08 05 01* waste isocyanates

15 01 10* packaging containing residues of or contaminated by

dangerous substances

14. SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

Not regulated for transport

15. SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006

Spoiler Adhesive Component B; 4,4'methylenediphenyl diisocyanate, oligomers

3(b) Substances or mixtures fulfilling the criteria for any of the following hazard
classes or categories set out in Annex I to Regulation (EC) No 1272/2008:
Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or
on development, 3.8 effects other than narcotic effects, 3.9 and 3.10

4,4'-methylenediphenyl diisocyanate

56. Methylenediphenyl diisocyanate (MDI)

4,4'-methylenediphenyl diisocyanate 56(a) Methylenediphenyl diisocyanate (MDI) isomers: 4,4'-Methylenediphenyl

diisocyanate

4,4'-methylenediphenyl diisocyanate 74. Diisocyanates, O = C=N-R-N = C=O, with R an aliphatic or aromatic

hydrocarbon unit of unspecified length

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

VOC (EU) 0 %

Other information, restriction and prohibition regulations

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. For details, refer to section 3 and 8.

Seveso Information Not applicable

National regulations

No additional information available.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

16. SECTION 16: Other information

Indication of changes

Section 1 - Section 16.

Abbreviations and acronyms	s
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
AGW	Occupational exposure limit value
ATE	Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)
BAM	Federal Institute for Materials Research and Testing, Germany
BAT	Maximum permissible concentration of biological working substances.
BCF	Bio-concentration factor.
BLV	Biological limit values
BLV	Biological limit values (BGW, Austria)
BMGV	Biological Monitoring Guidance Value (EH40,UK).
BOD5	Biochemical oxygen demand within 5 days
BOD	Biochemical oxygen demand
bw	Body weight.
calcd.	Calculated
CAS	Chemical Abstract Service.
CEN	European Committee for Standardization
CESIO	European Committee on Organic Surfactants and their Intermediates.

COD Chemical oxygen demand

CLP Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification,

labeling and packaging of substances and mixtures.

CMR Carcinogenic, Mutagenic or Reproduction Toxic Substances

CSA Chemical safety assessment
CSR Chemical Safety Report.

DMEL Derived Minimum Effect Level.

DNEL Derived no effect level
EAC European waste catalogue
EC European community
EC50 Effective concentration

EINECS European Inventory of Existing Commercial Chemical Substances.

ELINCS European List of Notified Chemical Substances.

EN European norm.

ERC (Environmental Release category)

EU European Union

GLP Good Laboratory Practice.

GHS Globally Harmonized System of Classification and Labeling of Chemicals.

GW/VL Occupational exposure limit value.

GW-kw/VL-cd Occupational exposure limit value - short term.

GW-M/VL-M Occupational exposure limit value - "Ceiling".

IATA International Air Transport Association

IBC code International Bulk Chemical (Code) (International Code for the Construction and Equipment of

Ships carrying Dangerous Chemicals in Bulk).

ICAO International Civil Aviation Organization

IC50 Inhibition Concentration 50%.

IECSC Inventory of Existing Chemical Substances in China.

IMDG International Maritime Dangerous Goods ISO International Standards Organization.

IUPAC International Union of Pure and Applied Chemistry

LC50 Lethal Concentration 50%.

LCLo Lowest published lethal concentration.

LD50 Lethal Dose 50%.

LOAEL Lowest Observed Adverse Effect Level LOEC Lowest observable effect concentration.

LOEL Lowest observable effect level.

LQ Limited quantities

TRK-Kzw Threshold limit value - Short-term exposure limit / Technical reference concentration - short-

time value, Austria.

MAK-Mow Maximum allowable workplace concentration – instantaneous value, Austria.

MAK-Tmw, TRK-Tmw Maximum allowable workplace concentration – daily mean value / Technical standard

concentration - daily mean value, Austria.

MAK Threshold limit values Germany.

MARPOL International Convention for the Prevention of Pollution from Ships.

NOAEC No-Observed Adverse Effect Concentration

NOAEL No-Observed Adverse Effect Level
NOEC No-Observed Effect Concentration

NOEL no-observed-effect level

OECD Organisation for Economic Co-operation and Development

OEL Occupational Exposure Limits
PBT Persistent Bioaccumulative Toxic
PC (Chemical product PC (Chemical product category)

category)

PNEC Predicted No-Effect Concentration
POCP Photochemical ozone creation potential.

POP Persistent Organic Pollutants
PPE Personal protective equipment

Process category Process category

REACH Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006

concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID Regulations concerning the International Carriage of Dangerous Goods by Rail

SCL Specific concentration limit.
STEL Short-term Exposure Limit
STP Sewage treatment plant
SU (Sector of use)
SU (Sector of use)

SVHC Substance of Very High Concern.

TLV Threshold Limit Value

TRGS Technical Rules for Hazardous Substances (German Standard).

TWA Time Weighted Average

UVCB Substances of Unknown or Variable composition, Complex reaction products or Biological

materials

VbF Ordinance on Flammable Liquids, Austria

VOC Volatile organic compounds

vPvB Very Persistent and Very Bioaccumulative

WEL-TWA Workplace Exposure Limit-Long term exposure limit (8-hour TWA(=time weighted

average)reference period).

WEL-STEL Workplace Exposure Limit-Short term exposure limit (15-minute reference period).

Data sources REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND

OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006...

Training advice Normal use of this product shall imply use in accordance with the instructions on

the packaging

Full text of H- and EUH-statements

Acute Tox. 4 (Inhalation) Acute toxicity (inhal.), Category 4.

Carc. 2 Carcinogenicity, Category 2.

Eye Irrit. 2 Serious eye damage/eye irritation, Category 2.

Resp. Sens. 1 Respiratory sensitisation, Category 1.

Skin Irrit. 2 Skin corrosion/irritation, Category 2.

Skin Sens. 1 Skin sensitisation, Category 1.

STOT RE 2 Specific target organ toxicity — Repeated exposure, Category 2.

STOT SE 3 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation.

H315 Causes skin irritation..

H317 May cause an allergic skin reaction..
H319 Causes serious eye irritation..

H332 Harmful if inhaled...

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled..
H335 May cause respiratory irritation..
H351 Suspected of causing cancer..

H373

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

May cause damage to organs through prolonged or repeated exposure...

L 1		
Acute Tox. 4 (Inhalation)	H332	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Resp. Sens. 1	H334	Calculation method
Skin Sens. 1	H317	Calculation method
Carc. 2	H351	Calculation method
STOT SE 3	H335	Calculation method
STOT RE 2	H373	Calculation method

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Attachment to the Safety Data Sheet



Product Name: Spoiler Adhesive Component B

Ford Int. Ref. No.: 130445 REVISION DATE: 10.03.2021

Involved Products:

Finiscode Part number Container Size:

1 HU7J M2G376 CA 100 ml

Part of Kit:

2 176 271 HU7J M2G376 AA Spoiler Adhesive Kit – 2 Component D2-100