

REAR AXLE OIL SAE 75W-85



SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

ISSUE DATE: 07.08.2019
REVISION DATE: 27.09.2022
SUPERSEDES: 26.11.2019
VERSION: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Rear Axle Oil SAE 75W-85
Product code : Ford Internal Ref.:201220
SDS Number : 6177
Product use : Professional use

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Function or use category : Lubricant

1.2.2. Uses advised against

Restrictions on use : None known

1.3. Details of the supplier of the safety data sheet

Supplier

Ford-Werke GmbH
Edsel-Ford-Str. 2-14
50769 Cologne
Germany
+49 221 90-33333
sdseu@ford.com

Distributor

Ford Motor Company Ltd.
Parts Distribution Centre
Royal Oak Way South
NN11 8NT Daventry, Northants
United Kingdom
+44 1327 305 198

1.4. Emergency telephone number

+49 (0) 6132-84463 (GBK GmbH – 24/7)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Environmental hazards	Hazardous to the aquatic environment – H411 Chronic Hazard, Category 2	Toxic to aquatic life with long lasting effects.
-----------------------	---	--

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations

Hazard pictograms



Signal word

-

Hazard statements

H411

Toxic to aquatic life with long lasting effects.

Precautionary statements**Prevention**

P273 Avoid release to the environment.

Response

P391 Collect spillage.

EUH-statements

EUH208 - Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) . May produce an allergic reaction.

2.3. Other hazards

Other hazards which do not result in classification : Defatting of the skin.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

Chemical name	CAS- No EC- No Index No RRN	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Notes
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-XXXX	50 - < 75	Asp. Tox. 1, H304	(Note L)
Dec-1-ene, homopolymer, hydrogenated	68037-01-4 500-183-1 - 01-2119486452-34-XXXX	1 - < 5	Asp. Tox. 1, H304	
1-Propene, 2-methyl-, sulfurized	68511-50-2 270-943-2	1 - < 3	Aquatic Chronic 4, H413	
Polysulfides, di-tert-Bu	68937-96-2 273-103-3 - 01-2119540515-43-XXXX	1 - < 3	Skin Sens. 1B, H317 Aquatic Chronic 3, H412	(46 ≤C ≤ 100) Skin Sens. 1B, H317
Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched)	N/A 931-384-6 01-2119493620-38-XXXX	0,1 - < 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	(9.39 ≤C < 100) Skin Sens. 1, H317 (50 <C ≤ 100) Eye Irrit. 2, H319
(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines	1213789-63-9 627-034-4 - 01-2119473797-19-XXXX	0,25 - < 1	Acute Tox. 4 (Oral), H302 (ATE=500 mg/kg bodyweight) Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410	

Note L : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 'Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions — Dimethyl sulphoxide extraction refractive index method', Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms occur.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth thoroughly. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Not expected to present a significant inhalation hazard under anticipated conditions of normal use.
Symptoms/effects after skin contact	: Defatting, drying and cracking of skin.
Symptoms/effects after eye contact	: May cause moderate irritation. Redness.
Symptoms/effects after ingestion	: May cause: Diarrhea, Nausea.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a water jet since it may cause the fire to spread.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: pressure rise and possible bursting of container.
Hazardous decomposition products in case of fire	: Toxic fumes may be released. Carbon oxides (CO, CO ₂).

5.3. Advice for firefighters

Firefighting instructions	: Positive pressure self-contained breathing apparatus (SCBA) and structural fire-fighters protective clothing.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Wear appropriate protective equipment and clothing during clean-up. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Ventilate spillage area. Wear appropriate protective equipment and clothing during clean-up. Local authorities should be advised if significant spillages cannot be contained.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Keep unnecessary personnel away.

6.2. Environmental precautions

Avoid release to the environment. Avoid discharge into drains, water courses or onto the ground. Prevent further leakage or spillage if safe to do so. Inform appropriate managerial or supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak without risks if possible. Move containers from fire area if it can be done without personal risk.
- Methods for cleaning up : Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills in original containers for re-use.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For disposal of residues refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Protect material from direct sunlight. Avoid contact with skin and eyes. Avoid breathing mist or vapor. Wear personal protective equipment.
- Hygiene measures : Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in original tightly closed container. Store in a well-ventilated place. Keep cool. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s)

Grease. Lubricant.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Exposure limit values for the other components

ethylbenzene (100-41-4)

United Kingdom - Occupational Exposure Limits

Local name	Ethylbenzene
WEL TWA (OEL TWA) [1]	441 mg/m ³
WEL TWA (OEL TWA) [2]	100 ppm
WEL STEL (OEL STEL)	552 mg/m ³
WEL STEL	125 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Regulatory reference	EH40. HSE

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Distillates (petroleum), hydrotreated heavy paraffinic (64742-54-7)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	0.97 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	2.73 mg/m ³
Long-term - local effects, inhalation	5.58 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	0.74 mg/kg bodyweight/day
------------------------------------	---------------------------

PNEC (Oral)

PNEC oral (secondary poisoning)	9.33 kg/kg food
---------------------------------	-----------------

Polysulfides, di-tert-Bu (68937-96-2)

DNEL/DMEL (Workers)

Long-term - systemic effects, dermal	3.33 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	14.5 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, inhalation	2.6 mg/m ³
Long-term - systemic effects, dermal	1.66 mg/kg bodyweight/day

PNEC (Water)

PNEC aqua (freshwater)	0.24 µg/L
PNEC aqua (marine water)	0.024 µg/L
PNEC aqua (intermittent, freshwater)	0.002 mg/l

PNEC (Sediment)

PNEC sediment (freshwater)	0.94 mg/kg dwt
PNEC sediment (marine water)	0.094 mg/kg dwt

PNEC (Soil)

PNEC soil	1513 mg/kg dwt
-----------	----------------

PNEC (Oral)

PNEC oral (secondary poisoning)	6.66 mg/kg food
---------------------------------	-----------------

PNEC (STP)

PNEC sewage treatment plant	4.51 mg/l
-----------------------------	-----------

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)

DNEL/DMEL (Workers)

Acute - local effects, dermal	160 µg/cm ²
Long-term - systemic effects, dermal	12.5 mg/kg bodyweight/day
Long-term - local effects, dermal	160 µg/cm ²
Long-term - systemic effects, inhalation	4.28 mg/m ³

DNEL/DMEL (General population)

Acute - local effects, dermal	160 µg/cm ²
Long-term - systemic effects, oral	0.25 mg/kg bodyweight/day
Long-term - systemic effects, inhalation	1.09 mg/m ³
Long-term - systemic effects, dermal	6.25 mg/kg bodyweight/day
Long-term - local effects, dermal	160 µg/cm ²

PNEC (Water)

PNEC aqua (freshwater)	2.4 µg/L
PNEC aqua (marine water)	0.24 µg/L
PNEC aqua (intermittent, freshwater)	150 µg/L
PNEC aqua (intermittent, marine water)	15 µg/L

PNEC (Sediment)

PNEC sediment (freshwater)	12.9 µg/kg dw
PNEC sediment (marine water)	1.29 µg/kg dw

PNEC (Soil)

PNEC soil	1.17 µg/kg dw
-----------	---------------

PNEC (Oral)

PNEC oral (secondary poisoning)	10 mg/kg food
---------------------------------	---------------

PNEC (STP)

PNEC sewage treatment plant	24.33 mg/l
-----------------------------	------------

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

DNEL/DMEL (Workers)

Acute - local effects, inhalation	1 mg/m ³
Long-term - systemic effects, inhalation	0.38 µg/m ³
Long-term - local effects, inhalation	1 mg/m ³

DNEL/DMEL (General population)

Long-term - systemic effects, oral	40 µg/kg bw/day
Long-term - systemic effects, inhalation	0.035 mg/m ³

PNEC (Water)

PNEC aqua (freshwater)	0.26 µg/L
PNEC aqua (marine water)	0.026 µg/L
PNEC aqua (intermittent, freshwater)	1.6 µg/L

PNEC (Sediment)

PNEC sediment (freshwater)	3.76 mg/kg dwt
PNEC sediment (marine water)	0.376 mg/kg dwt

PNEC (Soil)

PNEC soil	10 mg/kg dwt
-----------	--------------

PNEC (STP)

PNEC sewage treatment plant	550 µg/L
-----------------------------	----------

8.1.5. Control banding

No additional information available

8.2. Exposure controls**8.2.1. Appropriate engineering controls****Appropriate engineering controls:**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment**Personal protective equipment:**

Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the protective equipment.

8.2.2.1. Eye and face protection

Eye protection:

Use eye protection to EN 166, designed to protect against liquid splashes. Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing. Long sleeved protective clothing

Hand protection:

The recommendation is only valid for the supplied product and the stated application. Special working conditions, like heat or mechanical strain, which deviate from the test conditions, can reduce the protective effect provided by the recommended glove

Material	Permeation	Thickness (mm)	Comments
Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.
In case of splash contact: Nitrile rubber (NBR)	6 (> 480 minutes)	0,4	Glove recommendation: Camatril Velours® 730 (Kächele-Cama GmbH, source of supply see www.kcl.de) or comparable product.

Other skin protection

Materials for protective clothing:

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. If the occupational exposure limit is exceeded: Filter type: A-P2

8.2.2.4. Thermal hazards

Thermal hazard protection:

Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases.

Other information:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Blue. Green.
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: > 190 °C Open cup [Cleveland]
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: Not available
Viscosity, kinematic	: 69 mm ² /s @ 40°C
Solubility	: insoluble in water.
Log Kow	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available

Density	: < 1 g/cm ³ @ 15°C
Relative density	: Not available
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Oxidising agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	: Based on available data, the classification criteria are not met
Acute toxicity (dermal)	: Based on available data, the classification criteria are not met
Acute toxicity (inhalation)	: Based on available data, the classification criteria are not met

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)	
--	--

LD50 oral	2000 mg/kg bodyweight
-----------	-----------------------

ATE CLP (oral)	500 mg/kg bodyweight
----------------	----------------------

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)	
--	--

LD50 oral rat	1689 mg/kg bw/day
---------------	-------------------

ATE CLP (oral)	500 mg/kg bodyweight
----------------	----------------------

Skin corrosion/irritation	: Based on available data, the classification criteria are not met
Serious eye damage/irritation	: Based on available data, the classification criteria are not met
Respiratory or skin sensitisation	: Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Based on available data, the classification criteria are not met
Carcinogenicity	: Based on available data, the classification criteria are not met (All hydrocarbons in this mixture: Note L is applicable (DMSO <3%), therefore no classification as carcinogen)

Reproductive toxicity : Based on available data, the classification criteria are not met
STOT-single exposure : Based on available data, the classification criteria are not met

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Based on available data, the classification criteria are not met

(Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines (1213789-63-9)

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Based on available data, the classification criteria are not met

Rear Axle Oil SAE 75W-85

Viscosity, kinematic : 69 mm²/s @ 40°C

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Based on available data, the classification criteria are not met

Hazardous to the aquatic environment, long-term (chronic) : Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) (N/A)

Biodegradation : 7.4 % (28 d, OECD TG 301 B)

12.3. Bioaccumulative potential

Dec-1-ene, homopolymer, hydrogenated (68037-01-4)

Log Pow : > 3

Log Kow : > 6.5

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Rear Axle Oil SAE 75W-85

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII.

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII.

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Other adverse effects : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this product

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). Dispose of in accordance with local regulations.

Waste treatment methods	: Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.
Additional information	: Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Ecology - waste materials	: Avoid discharge into drains, water courses or onto the ground.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

14.1. UN number or ID number

UN-No. (ADR)	: UN 3082
UN-No. (IMDG)	: UN 3082
UN-No. (IATA)	: UN 3082
UN-No. (ADN)	: UN 3082
UN-No. (RID)	: UN 3082

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
Proper Shipping Name (IATA)	: Environmentally hazardous substance, liquid, n.o.s. ((Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
Proper Shipping Name (ADN)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)
Proper Shipping Name (RID)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. ((Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines)

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 9
Danger labels (ADR)	: 9

IMDG

Transport hazard class(es) (IMDG)	: 9
Danger labels (IMDG)	: 9

IATA

Transport hazard class(es) (IATA)	: 9
Hazard labels (IATA)	: 9

ADN

Transport hazard class(es) (ADN)	: 9
Danger labels (ADN)	: 9

RID

Transport hazard class(es) (RID)	: 9
Danger labels (RID)	: 9

14.4. Packing group

Packing group (ADR)	: III
Packing group (IMDG)	: III
Packing group (IATA)	: III
Packing group (ADN)	: III
Packing group (RID)	: III

14.5. Environmental hazards

Dangerous for the environment	: Yes
Marine pollutant	: Yes
Other information	: No supplementary information available.

14.6. Special precautions for user

Overland transport

Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Packing instructions (ADR)	: P001, IBC03, LP01, R001
Hazard identification number (Kemler No.)	: 90
Tunnel restriction code (ADR)	: -
EAC code	: •3Z

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Packing instructions (IMDG)	: LP01, P001
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197, A215
ERG code (IATA)	: 9L

Inland waterway transport

Classification code (ADN)	: M6
Special provisions (ADN)	: 274, 335, 375, 601
Limited quantities (ADN)	: 5 L
Carriage permitted (ADN)	: T

Rail transport

Classification code (RID)	: M6
Special provisions (RID)	: 274, 335, 375, 601
Limited quantities (RID)	: 5L
Packing instructions (RID)	: P001, IBC03, LP01, R001
Hazard identification number (RID)	: 90

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
3(b)	Distillates (petroleum), hydrotreated heavy paraffinic ; Dec-1-ene, homopolymer, hydrogenated ; Polysulfides, di-tert-Bu ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) ; (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines ; Distillates

3(c) (petroleum), hydrotreated heavy naphthenic ; Distillates (petroleum), hydrotreated light paraffinic ; Distillates (petroleum), solvent-dewaxed light paraffinic ; Distillates (petroleum), solvent-dewaxed heavy paraffinic
Rear Axle Oil SAE 75W-85 ; 1-Propene, 2-methyl-, sulfurized ; Polysulfides, di-tert-Bu ; Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) ; (Z)-octadec-9-enylamine, C16-18-(even numbered, saturated and unsaturated)-alkylamines

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : Not applicable

Other information, restriction and prohibition regulations : Directive 92/85/EEC on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding as amended. Directive 94/33/EC on the protection of young people at work, as amended. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended. For details, refer to section 3 and 8.

Directive 2012/18/EU (SEVESO III)

Seveso Additional information : Not applicable

Seveso III Part I (Categories of dangerous substances)

	Qualifying quantity (tonnes)	
	Lower-tier	Upper-tier
E2 Hazardous to the Aquatic Environment in Category Chronic 2	200	500

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes:

Section 1 - Section 16.

Abbreviations and acronyms

ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
DPD	Dangerous Preparations Directive 1999/45/EC
DSD	Dangerous Substances Directive 67/548/EEC
EC50	Median effective concentration
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet

STP	Sewage treatment plant
TLM	Median Tolerance Limit
vPvB	Very Persistent and Very Bioaccumulative
OEL	Occupational Exposure Limit
RRN	REACH Registration no.
CAO	Cargo Aircraft Only
PCA	Passenger and Cargo Aircraft

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H- and EUH-statements

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment – Chronic Hazard, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains Reaction products of bis(4-methylpentan-2-yl)dithiophosphoric acid with phosphorus oxide, propylene oxide and amines, C12-14-alkyl (branched) . May produce an allergic reaction.
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Aquatic Chronic 2	H411	Calculation method
-------------------	------	--------------------

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.



Attachment to the Safety Data Sheet

Product Name: Rear Axle Oil SAE 75W-85

Ford Int. Ref. No.: 201220

Revision Date: 27.09.2022

Involved Products:

Finiscode	Part number	Container Size:
1 2 433 507	EU7J M2C942 AB	1 l